

Safety Data Sheet (SDS)

Advanced Carbonate Technologies (ACT), LLC

ActProMin SA, BC, PP

SDS Number: 690

Revision Date: 8/13/2016

Page 1 of 9

1 PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Advanced Carbonate Technologies (ACT), LLC
 ActProMin
 2689 Hwy. 20
 Marysville, CA 95901

Contact: Advanced Carbonate Technologies (ACT),
Phone: +1 (530) 741-0873
Fax: +1 (530) 741-0876
Email: info@actnevada.com
Web: www.actnevada.com


Product Name: ActProMin SA, BC, PP
Revision Date: 8/13/2016
Version: 1
SDS Number: 690
Common Name: Calcium Carbonate, Crushed Limestone - Solid
CAS Number: MIXTURE
Product Code: ActProMin SA, BC, PP
Chemical Family: Limestone
Chemical Formula: CaCO3 (75-80%), MgCO3 (6-10%), SiO2 (4-17%)
Synonyms: Sedimentary Rock, Crushed Limestone
Product Use: Crushed limestone is used for Scientific, Agricultural, Building Construction, Polymerization and Processing Applications.

Domestic Emergency Phone: 1-800-373-7542 (24-Hour ER, Hazmat Service)
International Emergency Phone: 1-484-951-2432 (24-Hour ER, Hazmat Service)

2 HAZARDS IDENTIFICATION

NFPA:
 HMIS III:

Health = 1, Fire = 0, Reactivity = 0
 H*1/F0/PH0



HMIS III	
HEALTH	1
FLAMMABILITY	0
PHYSICAL HAZARDS	0
PERSONAL PROTECTION E Safety Glasses, Gloves, Dust Respirator	

PERSONAL PROTECTION INDEX													
A		G											
B		H											
C		I											
D		J											
E		K											
F		X	Consult your supervisor or S.O.P. for "SPECIAL" handling directions										
A		n		O		p		q		r		S	
t		u		w		y		z		Additional Information			

Safety Data Sheet (SDS)

Advanced Carbonate Technologies (ACT), LLC

ActProMin SA, BC, PP

SDS Number: 690

Revision Date: 8/13/2016

Page 2 of 9

GHS Signal Word:
DANGER

GHS Hazard Pictograms:



GHS Classifications:

Health, Skin corrosion/irritation, 2
Health, Serious Eye Damage/Eye Irritation, 2 A
Health, Carcinogenicity, 1 A
Health, Specific target organ toxicity - Repeated exposure, 2

GHS Phrases:

H315 - Causes skin irritation
H319 - Causes serious eye irritation
H350 - May cause cancer
H373 - May cause damage to organs through prolonged or repeated exposure

GHS Precautionary Statements:

P260 - Do not breathe dust.
P262 - Do not get in eyes, on skin, or on clothing.
P264 - Wash skin thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P302+352 - IF ON SKIN: Wash with soap and water.
P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338 - IF IN EYES: DO NOT RUB. Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
P333+313 - If skin irritation or a rash occurs: Get medical advice/attention.
P337+313 - If eye irritation persists: Get medical advice/attention.
P362 - Take off contaminated clothing and wash before reuse.
P501 - Dispose of contents/container to an approved waste disposal plant.

3

COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas #	Percentage	Chemical Name
1317-65-3	90-99.9%	Calcium carbonate
N/A	0-9.9%	Proprietary, non-hazardous, non-regulated*
14808-60-7	0.1-1%	Silica, crystalline quartz

*Balance of ingredients are non-hazardous, as defined by OSHA 29CFR1910.1200 or the Globally Harmonized System of Classification and Labeling of Chemicals (GHS), or hazardous in less than 1% concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory/skin sensitizers).

Safety Data Sheet (SDS)

Advanced Carbonate Technologies (ACT), LLC

ActProMin SA, BC, PP

SDS Number: 690

Revision Date: 8/13/2016

Page 3 of 9

4 FIRST AID MEASURES

- Inhalation:** Blow nose to remove substance from nasal passages. Give oxygen or artificial respiration if needed. If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.
- Skin Contact:** Wipe/brush off as much chemical as possible from skin BEFORE flushing skin with water. Promptly flush skin with water for at least 15 minutes to ensure all chemical is removed. If reddening and/or a rash develops and/or persists, obtain medical attention.
- Eye Contact:** Do NOT rub eyes. Flush with large amounts of water for at least 15 minutes, lifting upper and lower lids occasionally. If irritation persists, obtain medical attention.
- Ingestion:** No need for first aid is anticipated. If symptoms develop, obtain medical attention. Do NOT induce vomiting unless instructed to do so by medical personnel.

Most important symptoms and effects, both acute and delayed:

The most important known symptoms and effects are described in the labelling (see Section 2) and/or Section 11. In cases of extreme exposure, Calcium Carbonate may cause hypercalcemia, silicosis and pneumoconiosis. Hypercalcemia is characterized by abnormally high levels of Calcium in the circulating blood. Prolonged inhalation of crystalline silica dust may result in silicosis. Silicosis is a disabling pulmonary fibrosis characterized by fibrotic changes and miliary nodules in the lungs and may be accompanied by a dry cough, shortness of breath, emphysema, decreased chest expansion, and increased susceptibility to tuberculosis. In advanced stages, loss of appetite, pleuritic pain, and total incapacity to work may occur. Advanced silicosis may result in death due to cardiac failure or destruction of lung tissue. Crystalline silica is classified as Group 1 "Known to be carcinogenic to humans" by the IARC and "Sufficient evidence" of carcinogenicity by the NTP. The chronic health risks are associated with respiring particles of 3-4 microns over protracted periods of time. Currently, there is a limited understanding of the mechanisms of crystalline silica toxicity, including its mechanisms for lung carcinogenicity. Additional studies are needed to determine whether the cell transforming activity of quartz is related to its carcinogenic potential.

Indication of any immediate medical attention and special treatment needed:

No data available.

5 FIRE FIGHTING MEASURES

- Flammability:** Not flammable
- Flash Point:** DNA
- Flash Point Method:** DNA
- Burning Rate:** No data available
- Autoignition Temp:** No data available
- LEL:** DNA
- UEL:** DNA

Extinguishing Media:

Limestone does not burn. Use extinguishing media appropriate for surrounding fire conditions.

Special Hazards Arising From the Substance or Mixture:

Calcium Oxides
Carbon Oxides
Magnesium Oxides
Silicon Oxides

Advice for Firefighters:

Firefighters should wear full-face, positive-pressure respirators.

Safety Data Sheet (SDS)

Advanced Carbonate Technologies (ACT), LLC

ActProMin SA, BC, PP

SDS Number: 690

Revision Date: 8/13/2016

Page 4 of 9

Further Information:

If incinerated, may release toxic fumes.
Use water spray to damp down dust.
See Section 7 for more information on safe handling.
See Section 8 for more information on personal protection equipment.
See Section 13 for disposal information.

6

ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Use personal protective equipment, including dust respirator.
Avoid dust formation.
Avoid breathing dust.
Keep from contacting skin or eyes.
Ensure adequate ventilation.
Evacuate personnel to safe areas.

Environmental precautions:

Prevent further release (leakage/spillage) if safe to do so.

Methods and materials for containments and cleaning up:

Pick up and arrange disposal without creating dust.
Sweep up, shovel or collect spillage with an electrically protected vacuum cleaner.
Place contaminated material into suitable, closed containers for disposal.
Dispose of contaminated material according to Section 13.
After spillage has been collected, area may be flushed with water or wet-brushed.
Ensure adequate ventilation.

Reference to other sections:

Comply with federal, state and local regulations on reporting spills.
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for information on proper disposal.

7

HANDLING AND STORAGE

Handling Precautions:

Avoid formation of dust during saw cutting.
Avoid breathing dust during saw cutting.
Avoid contact with eyes, skin, or clothing.
Keep containers closed when not in use.
Do not expose containers to open flame or excessive heat.
Do not puncture or drop containers.
Handle with care and avoid spillage on the floor.
Keep material out of reach of children.
Keep material away from incompatible materials.
Wash thoroughly after handling.
Ensure adequate ventilation.

Storage Requirements:

Keep away from heat, sparks and flames.
Store in a dry area.
Store away from strong acids, strong oxidizing agents, Fluorine, Boron Trifluoride, Chlorine Trifluoride, Manganese Trifluoride, Oxygen Difluoride, Hydrofluoric acid, Magnesium and

Safety Data Sheet (SDS)

Advanced Carbonate Technologies (ACT), LLC

ActProMin SA, BC, PP

SDS Number: 690

Revision Date: 8/13/2016

Page 5 of 9

Aluminum.

8

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use local exhaust at filling zones and where leakage and dust formation is probable. Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

Personal Protective Equip: Eye/face protection:
When saw cutting material use safety glasses, gloves and dust respirator according to HMIS PP, E. All safety equipment should be tested and approved under appropriate government standards such as NIOSH (US) or EN 166 (EU).

Skin protection:
Handle with gloves made from water-impermeable materials. Barrier creams should not be used in place of gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact. Dispose of contaminated gloves according to applicable laws and laboratory practices.

Body Protection:
Chemically resistant gloves and safety glasses are recommended. Type of protective equipment should be selected based on concentration amount and conditions of use of this material.

Respiratory protection:
Use of a dust respirator is highly recommended. A full-face dust/vapor respirator may be required as backup to engineering controls when proper engineering controls are not in place to keep TLV and PEL limits below defined thresholds. All respiratory equipment must either be NIOSH/MSHA-approved (under 30 CFR 11) or NIOSH-approved (under 42 CFR 84).

Control of environmental exposure:
Prevent leakage or spillage if safe to do so. Do not let material enter drains.

Components with workplace control parameters:

Component(s): Calcium Carbonate
CAS No(s): 1317-65-3
USA OSHA (TWA/PEL): 15 mg/m³ (Total Dust)
USA OSHA (TWA/PEL): 5 mg/m³ (Respirable Fraction)
USA ACGIH (TWA/TLV): 10 mg/m³
USA NIOSH (TWA/REL): 10 mg/m³

Component(s): Silica, crystalline quartz
CAS No(s): 14808-60-7
USA OSHA (TWA/PEL, General Industry): 30 mg/m³ (%SiO₂+2, Total Dust, 8 hours)
USA OSHA (TWA/PEL, General Industry): 10 mg/m³ (%SiO₂+2, Respirable Fraction, 8 hours)
USA OSHA (TWA/PEL, General Industry): 250 mppcf* (%SiO₂+5)
USA OSHA (TWA/PEL, Construction Industry): 250 mppcf* (%SiO₂+5)
USA OSHA (TWA/PEL, Shipyard Employment): 250 mppcf* (%SiO₂+5)
USA ACGIH (TWA/TLV): 0.025 mg/m³
USA NIOSH (TWA/REL): 0.050 mg/m³
Cal/OSHA (TWA/PEL): 0.10 mg/m³

Safety Data Sheet (SDS)

Advanced Carbonate Technologies (ACT), LLC

ActProMin SA, BC, PP

SDS Number: 690

Revision Date: 8/13/2016

Page 6 of 9

*mppcf = Millions of particles per cubic foot of air

Biological occupational exposure limits:

Contains no substances with biological occupational exposure limits values.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	White, Solid	Odor:	Odorless
Physical State:	Solid	Molecular Formula:	MIXTURE
Odor Threshold:	Not determined	Solubility:	Insoluble
Particle Size:	Not determined	Softening Point:	Not determined
Spec Grav./Density:	2.4 - 2.9 g/cm ³	Percent Volatile:	0%
Viscosity:	Not determined	Heat Value:	Not determined
Sat. Vap. Conc.:	DNA	Freezing/Melting Pt.:	825 - 900 °C (1517 - 1652 °F)
Boiling Point:	Not determined	Flash Point:	DNA
Flammability:	(solid, gas): Not flammable	Octanol:	Not determined
Partition Coefficient:	Not determined	Vapor Density:	(air = 1): Not determined
Vapor Pressure:	(mm Hg @ 20 °C): 0	VOC:	DNA
pH:	Suspension: 8.0 - 9.0	Bulk Density:	Not determined
Evap. Rate:	DNA	Auto-ignition Temp:	Not determined
Molecular weight:	MIXTURE	UFL/LFL:	DNA
Decomp Temp:	Not determined		

10 STABILITY AND REACTIVITY

Stability:	Product is stable under normal conditions.
Conditions to Avoid:	Incompatibilities, flames, ignition sources.
Materials to Avoid:	Strong acids, strong oxidizing agents, Fluorine, Boron Trifluoride, Chlorine Trifluoride, Manganese Trifluoride, Oxygen Difluoride, Hydrofluoric acid, Magnesium and Aluminum.
Hazardous Decomposition:	Oxides of Calcium, Carbon, Magnesium and Silicon.
Hazardous Polymerization:	Will not occur.

11 TOXICOLOGICAL INFORMATION

Component(s): Calcium carbonate; Silica, crystalline quartz
CAS No(s): 1317-65-3; 14808-60-7

Acute Toxicity:
LD50 Oral - Rat: 6,450 mg/kg

Skin Corrosion/Irritation: Causes skin irritation.

Serious Eye Damage/Eye Irritation: Causes severe eye irritation.

Respiratory or Skin Sensitation: No data available.

Germ Cell Mutagenicity: No data available.

Carcinogenicity: This product is or contains a component that is classifiable as to its carcinogenicity to humans based on its

Safety Data Sheet (SDS)

Advanced Carbonate Technologies (ACT), LLC

ActProMin SA, BC, PP

SDS Number: 690

Revision Date: 8/13/2016

Page 7 of 9

IARC, ACGIH, NTP or OSHA classification (Silica, crystalline quartz). Limited evidence of carcinogenicity in human studies.

IARC: 1 - Group 1: Carcinogenic to humans (Silica, crystalline quartz).

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: Known to be a human carcinogen (Silica, crystalline quartz).

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive Toxicity: No data available.

Specific Target Organ Toxicity - Single Exposure: No data available.

Specific Target Organ Toxicity - Repeated Exposure: Inhalation - May cause damage to organs through prolonged or repeated inhalation exposure.

Aspiration Hazard: No data available.

Additional Information:

Component: Calcium carbonate; RTECS: EV9580000

Component: Silica, crystalline quartz; RTECS: VV7330000

12

ECOLOGICAL INFORMATION

Component(s): Calcium carbonate; Silica, crystalline quartz

CAS No(s): 1317-65-3; 14808-60-7

Toxicity:

Toxicity to fish:

No data available

Toxicity to daphnia and other aquatic invertebrates:

No data available

Persistence and Degradability:

No data available

Bioaccumulative potential:

No data available

Mobility in Soil:

No data available

Results of PBT and vPvB assessment:

Not required/conducted

Other Adverse Effects:

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. This material does not have any recognizable toxicity to plants or animals.

Safety Data Sheet (SDS)

Advanced Carbonate Technologies (ACT), LLC

ActProMin SA, BC, PP

SDS Number: 690

Revision Date: 8/13/2016

Page 8 of 9

13 DISPOSAL CONSIDERATIONS

Product: Hazardous wastes shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution, release into the environment or damage to people and animals. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated Packaging: Dispose of as unused product.

14 TRANSPORT INFORMATION

DOT (US)

Non-regulated material, solid

IMDG

Non-regulated material, solid

IATA

Non-regulated material, solid

15 REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

*Calcium carbonate (1317653 90-99.9%) MASS, NJHS, OSHAWAC, PA, TSCA, TXAIR

*Silica, crystalline quartz (14808607 0.1-1%) MASS, NJHS, NRC, OSHAWAC, PA, PROP65, SARA311/312, TSCA, TXAIR

REGULATORY KEY DESCRIPTIONS

MASS = MA Massachusetts Hazardous Substances List
NJHS = New Jersey Right to Know Hazardous Substances
NRC = Nationally Recognized Carcinogens
OSHAWAC = OSHA Workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
PROP65 = CA Prop 65
SARA311/312 = SARA 311/312 Toxic Chemicals
TSCA = Toxic Substances Control Act
TXAIR = TX Air Contaminants with Health Effects Screening Level

Safety Data Sheet (SDS)

Advanced Carbonate Technologies (ACT), LLC

ActProMin SA, BC, PP

SDS Number: 690

Revision Date: 8/13/2016

Page 9 of 9

16

OTHER INFORMATION

Disclaimer:

The data in this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material in any process. The information set forth herein is furnished free of charge and is based on technical data that Advanced Carbonate Technologies (ACT), LLC believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Since conditions of use are outside of Advanced Carbonate Technologies (ACT), LLC's control, Advanced Carbonate Technologies (ACT), LLC makes no warranties, expressed or implied, and assumes no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe upon, any patents.

Preparation Information:

GHS Conversion Services
www.ghsconversionservices.com
(414) 336-2546